

WL7 Firewall®

Stylish design, high-tech features and a plentiful source of ice-cold purified water



Unrivaled performance from the world-class point-of-use (POU) water system

This advanced water purification system combines refined engineering and high-tech features in a robust and reliable machine. The WL7 Firewall (WL7 FW) can dispense a large volume of ice-cold and bright sparkling water. Ideal to satisfy all the hydration needs of the busiest workplaces.

Leading technology

The WL7 FW features four core technologies:



High performance filtration

Waterlogic's filters offer the best-in-class filtration, guaranteeing premium quality water with every drop.



Firewall

Waterlogic's patented and certified Firewall technology features a highly effective UV antimicrobial purification system that acts all the way through to the point of dispense. **Firewall guarantees water free from viruses and bacteria up to 99.9999% and tested effective against COVID-19.**



Ice Bath cooling technology

The new Ice Bath water cooling system delivers high volumes of ice-cold water, offering the most consistently cold water of the Waterlogic range.

Class leading user experience

Designed to offer the best-in-class user experience, the WL7 FW presents a large dispense area, and features a visually engaging screen interface connected to an intuitive water selector gear, that allows the user to easily choose between five types of water.

*Firewall technology has been rigorously tested by a team of microbiologists from University of Arizona, and test results have demonstrated that Firewall is effective at inactivating the human form of the COVID-19 strain, with a colony reduction of over 99.999%.

Features

NSF 55 Class A and NSF P231 certified Firewall, patented UVC technology, that reduces the risks of viruses, cysts and pathogenic bacteria, purifying the water up to 99.9999%

Ice Bath cooling technology for abundance of highly purified ice-cold water

Sparkling system, engineered to deliver supreme quality of ice-cold effervescent water, comparable to even the finest bottled water

User interface with 5" full color LED display featuring machine status bar and water dispensing options

The ergonomic dispense area can accommodate tall water vessels and sports bottles

Maximum service efficiency, achieved via the self diagnostic system and QR code for instant access to the service manual via smart device

Versatile base cabinet converts the unit from countertop to freestanding, and offers filter and CO₂ storage space

Filter and UV fault indicators, as well as other system diagnostics for peace of mind

Leak prevention system provides extra protection and reduces risks of accident

Programmable energy saving sleep mode to significantly reduce power consumption when the unit is not in use

Water options

cold	sparkling	ambient	hot	extra hot
1				
2				

Number of users



Tested and certified

Firewall technology is certified by IAPMO R&T to NSF/ANSI 55 Class A, NSF P231, US EPA, NSF/ANSI 372 and CSA B483.1.



Waterlogic International Limited and WLI Trading Limited reserve the right in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates.

Technical specifications

Types available

Freestanding and countertop

Dimensions

15.70"/399 mm (W) x 50"/1269 mm (H) x 20.50"/519 mm (D) (Freestanding)
15"/381 mm (W) x 17"/427 mm (H) x 20.50"/519 mm (D) (Countertop)

Dispensing area height

10.74"/273 mm

Weight

103 lbs/47 KG freestanding
66 lbs/30 KG countertop

Filtration options*

1x Carbon Block (CBC), certified to NSF/ANSI-53 for cysts and asbestos reduction; (CBC for cysts, asbestos and lead reduction are also available)
1x Granular Activated Carbon (GAC), certified to NSF/ANSI-42;
Optional reverse osmosis (RO) system (Freestanding version only)

*dependent on local water conditions

Storage capacity

Cold only: 1.2 gal/4.5 liters
Cold and sparkling: 1 gal/3.8 liters

Storage capacity

Hot: 0.4 gal/1.5 liter

Dispensing capacity

(Cold only)
Up to 4.5 gal (17 L)/h
below 8°C
(Cold and sparkling)
Sparkling: Up to 3.7 gal (14 L)/h
below 8°C
Cold: Up to 4.0 gal (15 L)/h

Compressor

USA compressor (R134a): 97W

Water temperature output

Cold: 41 °F/ 5 °C
Hot: 167-199.4 °F/ 75-93 °C
Extra hot: 176-203 °F/ 80-95 °C



Call us today

Waterlogic Canada

Tel: 905-625-4488
Toll Free: 1-855-625-4488

87 Sharer Road
Vaughan ON, L4L 8Z3

customercare@waterlogiccanada.ca

For more information, visit waterlogiccanada.ca