

WL2 Firewall®

Excellent purifying performance,
easy operation and stylish design



R600a gas

**Zero
environmental
impact**

Purified water for the workplace

With a choice of hot, cold and ambient water, the WL2 Firewall (WL2 FW) is the preferred solution for any small or medium size workplace looking for great tasting water, reliability and guaranteed quality.

Advanced technology

The WL2 FW features three core technologies:



High performance filtration

Waterlogic's filters are certified to stringent standards, carrying the Water Quality Association's (WQA) Gold Seal of approval, meaning they offer the best possible filtration. This guarantees each drop is as good as the last.



Firewall purification

Waterlogic's patented and exclusive Firewall technology utilises a highly effective UVC purification system that acts at the point of dispense. Firewall guarantees up to 99.9999% bacteria free water. Glass after glass.



BioCote® protection

The key plastic surfaces surrounding the dispensing area are infused with BioCote®, a silver ion additive that provides continuous antimicrobial protection against a broad spectrum of bacteria, mould and fungi, and reduces the risks of cross-contamination.

Certified purity for peace of mind

Firewall technology is exclusive to Waterlogic and has been tested and certified by the WQA to NSF/ANSI-55 Class A UV and NSF P231 protocol - no other water cooler features these standards of certification together. This means that Firewall technology delivers the safest water possible for the workplace.

Features

Firewall, patented UV technology reduces the risks of bacteria, viruses, and cysts purifying the water up to 99.9999%, 100% of the time

Large dispensing area suitable to accommodate sport bottles

Environmentally friendly refrigeration using R600a: naturally occurring refrigerant gas with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential)

LED UV lamp and hot and cold fault indicators for straightforward fault diagnosis and servicing

BioCote® protected dispensing area (including drip tray body, cold faucet and dispensing buttons)

External drainage options available for extended drip tray capacity

Water options

	cold	sparkling	ambient	hot	extra hot
1					
2					

Number of users

 Up to 30

Technical specifications

Types available

Freestanding and countertop

Dimensions

Freestanding:

349 mm (W) x 1024 mm (H) x 363 mm (D)

Countertop:

349 mm (W) x 473 mm (H) x 363 mm (D)

Dispensing area height

230 mm

Weight (Hot and cold models)

Countertop: 20-24 kg

Freestanding: 27-29 kg

Standard filtration supplied

Carbon block filter (CBC)

Storage capacity

Hot tank: 1.5 litres

Cold tank (Freestanding): 4 litres

Cold tank (Countertop): 2 litres

Drip tray capacity

360 ml

Compressor

Compressor (R600a 1/8HP) 230V/50Hz

Water temperatures settings

Cold: 3°/ 5°/ 7° C (default 5°C)

Hot: 85-87°C (default 85°C)



Tested and certified

NSF/ANSI-55 Class A
Ultraviolet Microbiological
Water Treatment Systems

NSF P231
Protocol for
Microbiological Purifiers



CE QUALITY & SAFETY
GUARANTEED

*certificate may vary depending on different models or products

Waterlogic International Limited and WLI Trading Limited reserve the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLI Trading Ltd licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

Call us today

Waterlogic UK

+ 44 (0) 333 600 1845

enquiries@waterlogic.co.uk

Waterlogic IRE

1800 266 537

info@waterlogic.ie

www.waterlogic.co.uk

www.waterlogic.ie