

WL7 Firewall®

Stylish design, high-tech features and a plentiful source of ice-cold purified water



Available with
R600a gas

**Zero
environmental
impact**



Unrivalled performance from the world-class point-of-use (POU) water system

This advanced POU water purification system combines refined engineering and high-tech features in a robust and reliable machine. The WL7 Firewall (WL7 FW) can dispense up to five varieties of water, including a large volume of fresh, ice-cold sparkling water. Ideal to satisfy all the hydration needs of even the busiest workplaces.

Leading technology

The WL7 FW features four core technologies:



High performance filtration

Waterlogic filters offer 'best-in-class' filtration, guaranteeing premium purity with every drop.



Firewall

Waterlogic's patented and certified Firewall technology features a highly effective UV antimicrobial purification system that acts at the point of dispense. Firewall guarantees 99.9999% purified water. Glass after glass.



BioCote® protection

The WL7 FW key surfaces are infused with BioCote®, a silver ion additive able to inhibit microbial growth on the surface of the products helping to reduce unpleasant odours, degradation of key surfaces and the potential for cross contamination.



Ice Bath cooling technology

The new Ice Bath water cooling system delivers high volumes of ice-cold water, offering the most consistently cold water of the Waterlogic range.

Industry leading user experience

Designed to offer 'best-in-class' user experience, the WL7 FW features a large dispense area, alongside a user friendly screen interface and water selection dial, allowing users to easily choose between five types of water.

Features

NSF 55 Class A and NSF P231 certified Firewall, patented UVC technology, that reduces the risks of viruses and pathogenic bacteria, purifying the water up to 99.9999%
New Ice Bath cooling technology for abundance of highly purified ice-cold water
Sparkling system, engineered to deliver supreme quality of ice-cold sparkling water, comparable to even the finest bottled water
User interface with 5" full colour LED display featuring machine status bar and water dispensing options
The ergonomic dispense area can accommodate tall water vessels and sports bottles
BioCote® protected dispensing area (including nozzle, drip tray and dispensing button)
Versatile base cabinet converts the unit from countertop to freestanding, and offers filter and CO ₂ storage space
Filter and UV fault indicators and additional system diagnostics allow for straightforward fault diagnosis
Leak prevention system provides extra protection and reduces risks of accident
Programmable energy saving sleep mode to significantly reduce power consumption when the unit is not in use

Water options

	cold	sparkling	ambient	hot	extra hot
1					
2					

Number of users

 Up to 50

Tested and certified

NSF/ANSI-55 Class A
Ultraviolet Microbiological
Water Treatment Systems
NSF P231
Protocol for
Microbiological Purifiers



QUALITY & SAFETY
GUARANTEED

*certificate may vary depending on different models or products

Waterlogic International Limited and WLI Trading Limited reserve the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLI Trading Ltd licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

Technical specifications

Types available

Freestanding and countertop

Dimensions

381 mm (W) x 427 mm (H) x 519 mm (D) (Countertop)

399 mm (W) x 1269 mm (H) x 519 mm (D) (Freestanding)

Dispensing area height

273 mm

Weight

30 KG countertop

47 KG freestanding

Standard filtration supplied

Carbon block filter (CBC)

Storage capacity

Cold only: 4.5 litres

Cold and sparkling: 3.8 litres

Hot: 1.5 litres

Compressor

EU compressor (R600a): 100W

Water temperature settings

Cold: default set at 5°C

Hot: 75°C, 87°C, 93°C (Default set at 87°C)

Extra hot: 80°C, 87°C, +95°C (Default set at 95°C)



Call us today

Waterlogic UK

+44 (0) 333 600 1845

enquiries@waterlogic.co.uk

Waterlogic IRE

1800 266 537

info@waterlogic.ie

www.waterlogic.co.uk

www.waterlogic.ie