



WL2 Firewall™

Excellent purifying performance,
easy operation and stylish design

Simply pure water for the workplace

With a choice of hot and cold, or cold and ambient water the WL2 Firewall™ (WL2 FW) is the preferred solution for any small or medium size workplace looking for great tasting water, reliability and guaranteed quality.

Advanced technology

The WL2 FW features three core technologies:



High performance filtration

Waterlogic's filters are certified to stringent standards by IAPMO R&T, carrying the Water Quality Platinum Seal, meaning they offer the best possible filtration. This guarantees each drop is as good as the last.



Firewall purification

Waterlogic's patented and certified Firewall UVC purification system thoroughly purifies the water all the way through to the point of dispense, for microbiologically safe water. Guaranteed free from: up to 99.9999% bacteria, 99.99% viruses and 99.9% cysts.



BioCote® antimicrobial protection

The key plastic surfaces surrounding the dispensing area are infused with BioCote®, a silver ion additive that provides continuous antimicrobial protection against a broad spectrum of bacteria, mould and fungi, and reduces the risks of cross-contamination.



Certified purity for peace of mind

The Firewall technology has been certified by IAPMO R&T to NSF/ANSI-55 Class A and NSF P231 protocol, which is unique – no other water cooler features these standards of certification together. This means that Firewall technology delivers the safest water possible for the workplace.



*R600a gas
available on 220/240v
models only

Features

Firewall, patented UVC technology reduces the risks of bacteria, viruses, and cysts purifying the water up to 99.9999%

Dispensing area suitable to accommodate average size reusable bottles

Environmentally friendly refrigeration using R600a: naturally occurring refrigerant gas with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential)

Generous drip tray capacity for collecting accidental spillage

LED UV fault indicator for easier servicing and peace of mind

BioCote® protected dispensing area (including drip tray body, cold faucet and dispensing buttons)

Water options

	cold	sparkling	ambient	hot	extra hot
1					
2					

Technical specifications

Types available

Freestanding and countertop

Dimensions

Freestanding

349 mm/13.7" (W) x 1024 mm/40.3" (H) x 363 mm/14.3" (D)

Countertop

349 mm/13.7" (W) x 473 mm/18.6" (H) x 363 mm/14.3" (D)

Dispensing area height

230 mm/ 9"

Weight (Hot and cold models)

Countertop: 20-24 KG/ ~44-52 lbs

Freestanding: 27-29 KG/ ~59-61 lbs

Standard filtration supplied

Carbon

Storage capacity

Hot tank: 1.5 litres (0.4 US gal.)

Cold tank (Freestanding): 4 litres (1.06 US gal.)

Cold tank (Countertop): 2 litres (0.53 US gal.)

Drip tray capacity

360 ml (~12.7 fl oz)

Compressor

(R600a 1/8HP) 230V/50Hz

(R134a) 120V/60Hz

Water temperatures settings

Cold: 3°/ 5°/ 7° C (default 5° C)

Hot: 85-87° C/ 185-189° F (default 85° C)

Number of users 10 - 30

Contact us today

United Kingdom

www.waterlogic.co.uk

+44 (0) 333 323 2307

info@waterlogic.co.uk

Ireland

www.waterlogic.ie

+353 1466 0133

info@waterlogic.ie

Tested and certified



Firewall technology is certified by IAPMO R&T to **NSF/ANSI 55 Class A, NSF P231, US EPA Microbiological Guide Standard, NSF/ANSI 372 and CSA B483.1.**



*certificate may vary depending on different models or products