



WL3 Firewall™

Superior purification, proven performance and elegant design

The hydration station for the modern office

The WL3 Firewall™ (WL3 FW) by Waterlogic® brings a variety of refreshing purified water choices to the workplace, supplying cold, sparkling, hot and extra hot options, and powered by Firewall, Waterlogic's superior UVC purification technology.

Advanced technology

The WL3 FW features three core technologies:



High performance filtration

Waterlogic's filters are certified to stringent standards by IAPMO R&T, carrying the Water Quality Platinum Seal, meaning they offer the best possible filtration. This guarantees each drop is as good as the last.



Firewall purification

Waterlogic's patented and certified Firewall UVC purification system thoroughly purifies the water all the way through to the point of dispense, for microbiologically safe water. Tested 99.999% effective against COVID-19 and guaranteed free from: up to 99.9999% bacteria, 99.99% viruses, and 99.9% cysts.



BioCote® antimicrobial protection

The WL3 FW key surfaces are infused with BioCote®, a silver ion additive able to inhibit microbial growth on the surface of the products helping to reduce unpleasant odours, degradation of key surfaces and the potential for cross contamination.



High quality sparkling water system

WL3 FW is designed with a unique technology which delivers premium sparkling water. The system is engineered to remove any remaining fizzy water left in the pipes, preventing from reaching back into the sparkling tank so that the water doesn't go flat.



*R600a gas available on 220/240v models only

Features

Firewall, patented UVC technology reduces the risks of bacteria, viruses, and pathogens purifying the water up to 99.9999%

Superior quality sparkling water, safely purified to NSF standards

Touch sensitive control panel for easy operations

Environmentally friendly refrigeration using R600a*: naturally occurring refrigerant gas with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential)

Generous drip tray capacity for collecting accidental spillage

LED UV fault indicator for easier servicing and peace of mind

BioCote® protected dispensing area and key surfaces for greater hygiene

Water options

	cold	sparkling	ambient	hot	extra hot
1					
2					
3					
4					

Number of users 15 - 30

Contact us today

United Kingdom
www.waterlogic.co.uk
 +44 (0) 333 323 2307
 info@waterlogic.co.uk

Ireland
www.waterlogic.ie
 +353 1466 0133
 info@waterlogic.ie

Technical specifications

Types available

Freestanding and countertop

Dimensions (include feet)

Freestanding (CAS and HCA):
 393 mm/15.4" (W) x 1157 mm/45.5" (H) x 459 mm/18.1" (D)

Countertop (CAS and HCA):
 393 mm/15.4" (W) x 486 mm/19.1" (H) x 459 mm/18.1" (D)

Freestanding (HCS):
 391 mm/15.39" (W) x 1157 mm/45.5" (H) x 371 mm/14.6" (D)

Dispensing area height

220 mm/ 8.7"

Weight

Countertop: 22-27 KG/ ~48-59 lbs

Freestanding: 30-34 KG/ ~66-75 lbs

Standard filtration supplied

Carbon

Storage capacity

Cold tank (HCA Freestanding): 4 litres (1.06 US gal.)

Cold tank (HCA Countertop): 2 litres (0.53 US gal.)

Cold tank (HCS and CAS): 3 litres (0.8 US gal.)

Hot tank (Countertop): 1.5 litres (0.4 US gal.)

Hot tank (Freestanding): 2 litres (0.53 US gal.)

Sparkling tank: 0.8 litres (0.21 US gal.)

Compressor

220/240v 50Hz or 110/120v 60Hz

Water temperatures settings

Cold: 5°/ 41°F

Hot: 87°C/ 189°F

Extra Hot: 93°C/ 199°F

Tested and certified



Firewall technology is certified by IAPMO R&T to **NSF/ANSI 55 Class A, NSF P231, US EPA Microbiological Guide Standard, NSF/ANSI 372 and CSA B483.1.**

*certificate may vary depending on different models or products