

# WL2 Firewall®

Excellent purifying performance, easy operation, and stylish design



## The right choice for government

With a choice of hot and cold, the WL2 Firewall (WL2 FW) is the preferred solution for any small or medium-size government organization, looking for great-tasting water, reliability, and guaranteed quality.

## Advanced technology

The WL2 FW features three core technologies:



### High performance filtration

Waterlogic's filters are certified to stringent standards by IAPMO R&T and to NSF/ANSI-53 for the reduction of lead, asbestos, and cysts, meaning they offer the best possible filtration.



### Firewall®

Waterlogic's patented Firewall® technology features a highly effective UVC purification system that acts all the way through to the point of dispense. **Firewall® guarantees water free from viruses and bacteria up to 99.9999%. Guaranteed effective against COVID-19.**



### BioCote® protection\*

The key plastic surfaces, surrounding the dispensing area, are infused with BioCote®, a silver ion additive that provides an effective barrier against microbes like bacteria and mold, which may cause odors or staining.

## Certified purity for peace of mind

The Firewall technology has been certified by IAPMO R&T to NSF/ANSI-55 Class A UV and NSF P231 protocol, which is unique – **no other water cooler features these standards of certification together.** This means that **Firewall® technology delivers the safest water possible** for the workplace.

\*BioCote® technology does not protect users or others against disease causing bacteria, germs, viruses, or other harmful organisms. This technology is not a substitute for good hygiene and/or cleaning practices. BioCote® has not been tested or proven effective against SARS-CoV-2.

## Features

Firewall patented UV technology reduces the risks of bacteria, viruses, and pathogens, purifying the water up to 99.9999%

BioCote® reduces microbes up to 99.5% within 2 hours

Generous drip tray capacity for collecting accidental spillage

LED UV fault indicator for easier servicing and peace of mind

Dispensing area suitable to accommodate sport bottles

## Water options



## Number of users



10 - 30 (Freestanding)  
up to 10 (Countertop)



The WL2 FW is ideal for those who are or become physically challenged

The WL2 FW unit meets the Accessibility Guidelines for the Americans with Disabilities Act (ADA)

## Tested and certified

Firewall technology is certified by IAPMO R&T to NSF/ANSI 55 Class A, NSF P231, US EPA, NSF/ANSI 372 and CSA B483.1.



Waterlogic International Limited and WLI Trading Limited reserve the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLI Trading Ltd licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

## Technical specifications

### Types available

Freestanding and countertop

### Dimensions

Freestanding:

13.7" (W) x 40.3" (H) x 14.3" (D)

Countertop:

13.7" (W) x 18.6" (H) x 14.3" (D)

### Dispensing area height

9"

### Weight

Countertop: ~42 lbs

Freestanding: ~58 lbs

### Standard filtration supplied

Carbon block with lead, cyst, and asbestos reduction

### Storage capacity

Hot tank: 0.4 US gal

Cold tank (Freestanding): 1.06 US gal

Cold tank (Countertop): 0.53 US gal

### Drip tray capacity

12.70 fl oz/360 ml

### Compressor

Compressor (R134a) 120V/60Hz

### Water temperature settings

Cold: 37°/ 41°/ 45°F (default 41°F)

Hot: 185-189°F (default 185°F)



## Call us today



Waterlogic- Federal Government  
Tel: (800) 283-2024

3175 Bass Pro Drive  
Grapevine, TX 76051

[www.waterlogicfedgov.com](http://www.waterlogicfedgov.com)  
[fedgov@waterlogicusa.com](mailto:fedgov@waterlogicusa.com)

For more information, visit [www.waterlogicfedgov.com](http://www.waterlogicfedgov.com)