



WL290

High performance water dispenser for great quality water

Superior performance

The WL290 satisfies the needs for high volumes of cold and hot water, while delivering superb quality water. Specifically designed for conditions when reverse osmosis is needed, or where there might be low water pressure, the WL290 is a gravity fed machine with premium filtration and in-tank ultraviolet light built-in. The improved internal design and technology makes the WL290 perfect to supply quality water all day long in high traffic working environments and public places.

Advanced technology

The WL290 features three core technologies:



High performance filtration

This model can be configured with four-stage reverse osmosis filtration or multi-stage carbon filtration, depending on water conditions. These filtration processes effectively remove water contaminants and chlorine to improve water taste and odor.



In-tank UV sanitization

Waterlogic's in-tank UV technology acts against waterborne microorganisms and bacteria, dispensing great quality water, glass after glass.



BioCote®* product protection

The key plastic surfaces, surrounding the dispensing area, are infused with BioCote® technology, a silver ion additive that inhibits the growth of odor and stain causing microbes, such as bacteria and mold.



Simply great, clear water**

Free from fluoride, free from chlorine, and free from water-borne tastes and odors. (dependent on filters type and water conditions)

*BioCote® silver ion technology protects surfaces from odor- and stain-causing microbes. BioCote® does not protect users or others against bacteria, viruses, germs or other disease causing organisms. This technology is not a substitute for good cleaning practices. **Filtration results based on the use of RO, GAC, CBC, or sediment filters.

Features

Multiple filtration options: choice of reverse osmosis or carbon filtration to fit local water conditions

Large, chilled, recirculating reservoir for high capacity cold water production allows for 4x more cold water capacity

Gravity-fed storage tank provides additional stored water for the reverse osmosis system or for low pressure installations

The recirculating cold water system passes water by the in-tank UV light multiple times every hour to maintain the microbiological purity of the water

Programmable temperature settings for hot and cold options

GAC filter, fitted inside the cold reservoir, provides ongoing protection from bad tastes and odors

Fault indicators for easier servicing

Reservoir and dispensing area (including drip tray body, cold faucet, and user interface panel) are all protected by BioCote® technology against odor and stain causing microbes

Energy-saving sleep mode significantly reduces power consumption when the unit is not in use

Leak detection system provides extra protection and reduces risks of an accident

Water options

cold hot ambient hot extra hot



Technical specifications

Types available

Freestanding

Dimensions

15.39" (W) x 45.70" (H) x 14.40" (D)

Dispensing area height

9.0"

Weight

62 lbs

Recommended filtration

Reverse osmosis or 1 x carbon block (CBC), sediment, GAC, CBC with lead and cyst removal (dependent on local water conditions)

Storage capacity

Chilled reservoir: ~ 3 gal

Cold hybrid tank: ~ 1 gal

Total cold capacity: ~ 4 gal

Hot tank (500 Watt): ~½ gal

185° F (thermistor-controlled)

Compressor

110V/60Hz

Water temperatures settings

Cold: 37°/ 41°/44° F (default set at 41°F)

Hot: 176°/ 185°/ 199° F (default set at 185°F)

Dispensing capacity (Cold)

More than 2 gallons per hour

Number of users 50+

Contact us today

Waterlogic Commercial Products

www.waterlogicdealers.com

(800) 288-1891

customerservice@waterlogicsusa.com

3175 Bass Pro Drive
Grapevine, TX 76051

Tested and certified



*certificate may vary depending on different models or products