



WL2 Firewall® Tall

Excellent purifying performance,
easy operation, and stylish design

Purified water for your organization

With a choice of hot and cold, the WL2 Firewall® Tall is the preferred solution for any small or medium-sized workplace, looking for great-tasting water, reliability, and guaranteed quality.

Advanced technology

The WL2 FW Tall features three core technologies:



High performance filtration

The WL2 FW Tall features reverse osmosis filtration for the reduction of lead, asbestos, and cysts to give you the best possible filtration.



Firewall purification

Waterlogic's patented Firewall technology features a highly effective UVC purification system that acts all the way through to the point of dispense. **Firewall guarantees water free from viruses and bacteria up to 99.9999%. Guaranteed effective against COVID-19.**



BioCote®* product protection

The key plastic surfaces, surrounding the dispensing area are infused with BioCote® technology, a silver ion additive that inhibits the growth of odor and stain causing microbes, such as bacteria and mold.



Certified purity for peace of mind

The Firewall technology has been certified by IAPMO R&T to NSF/ANSI-55 Class A UV and NSF P231 protocol, which is unique – **no other water cooler features these standards of certification together.** This means that **Firewall technology delivers the safest water possible for the workplace.**

*BioCote® silver ion technology protects surfaces from odor- and stain-causing microbes. BioCote® does not protect users or others against bacteria, viruses, germs or other disease causing organisms. This technology is not a substitute for good cleaning practices.

Features

Firewall, patented UVC technology, reduces the risks of viruses, cysts, and pathogenic bacteria, purifying the water up to 99.9999%, 100% of the time

BioCote®* helps to keep Waterlogic dispensers fresh and clean by inhibiting the growth of odor causing microbes on their surface, such as bacteria and mold**

Generous drip tray capacity for collecting accidental spillage

LED UV fault indicator for easier servicing and peace of mind

Dispensing area suitable to accommodate sport bottles

Ready for hands-free pedal retrofit

Hot water safety double press via manually operated button or via hot pedal

Water options

cold

hot



Technical specifications

Types available

Freestanding

Dimensions

Freestanding
13.74" (W) x 46.3" (H) x 14.3" (D)

Dispensing area height

9"

Weight

Freestanding: ~58 lbs

Standard filtration supplied

Four-stage reverse osmosis filtration with a two-gallon bladder tank

Storage capacity

Hot tank: 0.4 gal
Cold tank (Freestanding): 1.06 gal

Drip tray capacity

12.70 fl oz

Compressor

Compressor (R134a) 120V/60Hz

Water temperature settings

Cold: 37°F / 41°F / 45°F (default set at 41°F)
Hot: 185-189°F (default set at 189°F)

Number of users 10-30

Contact us today

Waterlogic Americas
www.waterlogicausa.com
(855) 350-5518
info@waterlogicausa.com

3175 Bass Pro Drive,
Grapevine, TX 76051

Tested and certified



Firewall technology is certified IAPMO R&T to **NSF/ANSI 55 Class A, NSF P231, US EPA, NSF/ANSI 372 and CSA B483.1.**



*certificate may vary depending on different models or products