

WL500

A high-end unit for premium quality sparkling water



A comprehensive hydration solution for the modern workplace

Easy operation, robust design and a choice of four water dispensing options, make the WL500 the ideal dispenser for demanding environments, such as factories and medium to large offices, where quality water is in high demand.

Advanced technology

The WL500 features three core technologies:



High performance

Multi-stage filtration removes common water contaminants and chlorine to dramatically improve water taste and odor.



In-tank UV Sanitization

Waterlogic's in-tank UV technology acts against waterborne micro-organisms and bacteria, dispensing great quality water glass after glass.



BioCote® Protection

WL500 key surfaces are infused with BioCote®, a silver ion additive that provides an effective barrier against microbes like bacteria and mold, which may cause odors or staining.

High quality sparkling water system

WL500 is designed with a unique technology which reliably delivers sparkling water on demand. The system is engineered to remove any sparkling water left in the pipes, preventing it from reaching back into the tank so that the water doesn't go flat.

Features

Advanced carbonation technology to produce exceptional sparkling water

Versatile base cabinet converts the unit from countertop to freestanding, and offers additional storage space

The in-tank sanitizing system ensures water is exposed to the UV light to reduce bio-film build up and bacterial growth, restoring the microbiological purity of the water

Digital display with multiple language settings

BioCote® protected reservoir and dispensing area (including drip tray body, cold faucet, and buttons)

Leak detection and drip tray overflow alarm for added peace of mind

Energy saving sleep mode to significantly reduce power consumption when the unit is not in use

Water options

cold



sparkling



ambient

hot



extra hot



Number of users



30 - 50

Tested and certified



CE QUALITY & SAFETY GUARANTEED

Waterlogic International Limited and WLI Trading Limited reserve the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLI Trading Ltd licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

Technical specifications

Types available

Freestanding and tabletop

Dimensions

Freestanding:

16.81"/427mm (W) x 49.80"/1265mm (H) x 17.63"/448mm (D)

Tabletop:

16.81"/427mm (W) x 18.77"/477mm (H) x 17.63"/448mm (D)

Dispensing area height

6.75"/170mm

Weight

Freestanding: 104lbs/47kg

Tabletop: 35lbs/15.9kg

Standard filtration recommended

Carbon

Storage capacity

Cold tank: 3 liters

Sparkling tank: 1 liter

Hot tank: 1.6 liters

Compressor

120V (60 Hz)

Water temperature settings

Cold: 41°F/5° C

Hot: 189°F/87° C

Extra Hot: 203°F/95° C



Call us today

Waterlogic Commercial Products, LLC

Tel: 800-288-1891

11710 Stonegate Circle
Omaha, NE 68164

www.waterlogicsusa.com

customerservice@waterlogicsusa.com

For more information, visit www.waterlogic.com