



WL500

A high-end unit for premium quality sparkling water

A comprehensive hydration solution for the modern workplace

Easy operation, robust design, and a choice of four water dispensing options make the WL500 the ideal dispenser for demanding environments, such as factories and medium to large offices, where quality water is in high demand.

Advanced technology

The WL500 features three core technologies:



High performance filtration

Multi-stage filtration removes common water contaminants and chlorine to dramatically improve water taste and odor.



In-tank UV sanitization

Waterlogic's in-tank UV technology acts against waterborne microorganisms and bacteria, dispensing great quality water, glass after glass.



BioCote®* product protection

The key plastic surfaces surrounding the dispensing area are infused with BioCote®* technology, a silver ion additive that inhibits the growth of odor and stain causing microbes, such as bacteria and mold



High quality sparkling water system

WL500 is designed with a unique technology which reliably delivers sparkling water on demand. The system is engineered to remove any sparkling water left in the pipes, preventing it from reaching back into the tank so that the water doesn't go flat.

*BioCote® silver ion technology protects surfaces from odor- and stain-causing microbes. BioCote® does not protect users or others against bacteria, viruses, germs or other disease causing organisms. This technology is not a substitute for good cleaning practices.

Features

Advanced carbonation technology to produce exceptional sparkling water

Versatile base cabinet converts the unit from countertop to freestanding, and offers additional storage space

Optional cup holder available

Reservoir and dispensing area (including drip tray body, cold faucet, and buttons) are all protected by BioCote®* technology against odor and stain causing microbes

The in-tank sanitizing system ensures water is exposed to the UV light to reduce bio-film build-up and bacterial growth, restoring the microbiological purity of the water

Digital display with multiple language settings

Energy saving sleep mode to significantly reduce power consumption when the unit is not in use

Leak detection and drip tray overflow alarm for added peace of mind

Water options

cold sparkling ambient hot extra hot



Number of users: 1-50

Technical specifications

Types available

Freestanding and countertop

Dimensions

Freestanding
16.81" (W) x 49.80" (H) x 17.63" (D)

Countertop
16.81 (W) x 18.77" (H) x 17.63" (D)

Dispensing area height

6.75"

Weight

Freestanding: 104 lbs
Countertop: 35 lbs

Standard filtration recommended

Carbon

Storage capacity

Hot tank: 1.6 liters
Cold tank: 3 liters
Sparkling tank: 1 liter

Compressor

120V/60Hz

Water temperatures settings

Cold: 41°F (default)
Hot: 189°F
Extra Hot: 203°F

Contact us today

Waterlogic Commercial Products
www.waterlogicdealers.com
(800) 288-1891
customerservice@waterlogicausa.com

3175 Bass Pro Drive
Grapevine, TX 76051

Tested and certified

