



# WL7 Firewall<sup>®</sup>

Stylish design, high-tech features and a plentiful source of ice-cold purified water

## Unrivaled performance from the world-class point-of-use (POU) water system

This advanced water purification system combines refined engineering and high-tech features in a robust and reliable machine. The WL7 Firewall<sup>®</sup> (WL7 FW) can dispense up to five varieties of water, including large volumes of ice-cold and sparkling water. It's the ultimate choice in hydration to meet the needs of a hard-working office.

## Leading technology

The WL7 FW features four core technologies:



### High performance filtration

Waterlogic's filters are certified to stringent standards by IAPMO R&T and to NSF/ANSI-53 for the reduction of lead, asbestos, and cysts, meaning they offer the best possible filtration.



### Firewall purification

Waterlogic's patented Firewall technology features a highly effective UVC purification system that acts all the way through to the point of dispense. **Firewall guarantees water free from viruses and bacteria up to 99.9999%. Guaranteed effective against COVID-19.**



### BioCote<sup>®\*</sup> product protection

The key plastic surfaces, surrounding the dispensing area are infused with BioCote<sup>®</sup> technology, a silver ion additive that inhibits the growth of odor and stain causing microbes, such as bacteria and mold.



### Ice Bath cooling technology

The new ice bath water cooling system delivers high volumes of ice cold water.



## Industry leading user experience

Designed to offer the best-in-class user experience, the WL7 FW presents a large dispense area and features a visually engaging screen interface, connected to an intuitive water selector gear that allows the user to easily choose between five types of water.

\*BioCote<sup>®</sup> silver ion technology protects surfaces from odor- and stain-causing microbes. BioCote<sup>®</sup> does not protect users or others against bacteria, viruses, germs or other disease causing organisms. This technology is not a substitute for good cleaning practices.

## Features

Firewall, patented UVC technology, reduces the risks of viruses, cysts, and pathogenic bacteria, purifying the water up to 99.9999%, 100% of the time

Ice bath cooling technology for abundance of highly purified, ice-cold water

Sparkling system, engineered to deliver supreme quality of ice-cold effervescent water comparable to even the finest bottled sparkling water

User interface with 5" full color LED display, featuring machine status bar and water dispensing options

Programmable energy-saving mode to significantly reduce power consumption when the unit is not in use

The ergonomic dispense area can accommodate tall water vessels and sports bottles

Maximum service efficiency, achieved via the self diagnostic system and QR code for instant access to the service manual via smart device

Versatile base cabinet converts the unit from countertop to freestanding, and offers filter and CO<sub>2</sub> storage space

Filter and UV fault indicators, as well as other system diagnostics for peace of mind

Leak prevention system provides extra protection and reduces the risk of accidents

## Water options

	cold	sparkling	ambient	hot	extra hot
1					
2					

Number of users 50+

## Contact us today

Waterlogic Americas  
[www.waterlogicsusa.com](http://www.waterlogicsusa.com)  
(855) 350-5518  
[info@waterlogicsusa.com](mailto:info@waterlogicsusa.com)

3175 Bass Pro Drive,  
Grapevine, TX 76051

Waterlogic International Limited and WLI Trading Limited reserve the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLI Trading Ltd licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

## Technical specifications

### Types available

Freestanding (with base cabinet) and countertop

### Dimensions

Freestanding

15" (W) x 17" (H) x 20.5" (D) (Countertop)

15.7" (W) x 50" (H) x 20.5" (D) (Freestanding)

### Dispensing area height

10.74"

### Weight

66 lbs countertop

103 lbs freestanding

### Filtration options\*

1 x Carbon Block (CBC), certified to NSF/ANSI-53 for cysts and asbestos reduction; (CBC for cysts, asbestos and lead reduction are also available)

1 x Granular Activated Carbon (GAC), certified to NSF/ANSI-42; Optional reverse osmosis (RO) system (Freestanding version only)

\* dependent on local water conditions

### Storage capacity

Cold only: 1.2 gal

Cold and sparkling: 1 gal

### Storage capacity

Hot: 0.4 gal

### Dispensing capacity (Cold only)

Up to 4.5 gal/h

below 8°C

### Dispensing capacity (Cold and sparkling)

Sparkling: Up to 3.7 gal/h

below 8°C

Cold: Up 4.0 gal/h

### Compressor

USA compressor (R134a): 97W

### Water temperature settings

Cold: default set at 41°F

Hot: 167°F, 189°F, 199.4°F (Default set at 189°F)

Extra hot: 176°F, 189°F, 203°F (Default set at 203°F)

## Tested and certified



Firewall technology is certified IAPMO R&T to NSF/ANSI 55 Class A, NSF P231, US EPA, NSF/ANSI 372 and CSA B483.1.



\*certificate may vary depending on different models or products