



WLH2 Firewall[®] Bar Classe Series

Unparalleled dispensing and purification performance in an elegantly designed unit

Designed to provide a plentiful source of thoroughly purified, ice cold still and sparkling water, the WLH2 Firewall[®] Bar Classe Series is a robust, reliable and sophisticated dispenser, satisfying the water needs of environments where high volumes and flow are in high demand.

Leading technology



High flow performance filtration

The professional-grade filtration satisfies the need for dispensing high volumes of water, addressing color, taste, and odor for great tasting and high quality water.



Firewall purification

High flow Firewall UVC purification thoroughly purifies the water up to the point of dispense for microbiologically safe water. **Guaranteed free from: up to 99.9999% bacteria, 99.99% viruses (COVID-19), and 99.9% cysts.** Certified by IAPMO R&T to NSF 55 Class A and P231 standards for microbiological water purifiers.



Ice Bath cooling technology

The ice bath water cooling system delivers high volumes of consistent ice cold water, catering to environments where such a need is paramount.



BioCote[®]* technology

The bottle holders and floater mechanism are protected by BioCote[®]* antimicrobial technology, proven to inhibit the growth of microbes such as bacteria and mold



*BioCote[®] silver ion technology protects surfaces from odor- and stain-causing microbes. BioCote[®] does not protect users or others against bacteria, viruses, germs or other disease causing organisms. This technology is not a substitute for good cleaning practices.

Features

NSF 55 Class A and NSF P231 certified Firewall, patented UVC technology deactivates most viruses, cysts, and bacteria, thoroughly purifying the water up to 99.9999%.

Firewall UV lamp monitoring system guarantees consistent standards of water purification.

Sparkling system includes CO₂ gas pressure control and is engineered to deliver supreme quality, ice cold sparkling water, comparable to even the finest bottled water.

Electronic push buttons allow for continuous dispense (max 3 liters) or pre-set portion control to fill 750 ml and 1-liter size bottles. Sequential dispense (one pre-set dispense after the other from each tap) can also be set up for peak-time usage.

The ergonomic dispense area and the adjustable height drip tray are designed to accommodate various size vessels.

Circular bottle holders allow for accurate positioning of the bottles, preventing unnecessary water spillage.

Versatile base cabinet converts the unit from countertop to freestanding, and provides additional storage space.

Removable steel side plate facilitates air filter cleaning operations as dust and dirt can penetrate through the grid.

LED side panel displays filter, Firewall, and ice bath fault indicators as well as other system diagnostics give peace of mind and optimum service efficiency.

Programmable energy-saving sleep mode significantly reduces power consumption when the unit is not in use.

Water options

Cold Sparkling



Number of users 100+

Technical specifications

Types available

Countertop and freestanding with optional base cabinet

Both available on request with hands-free pedal operations

Dimensions

Countertop, including wheels:

15.74" (W) x 23.90" (H) x 23.22" (D)

Freestanding:

15.74" (W) x 54.80" (H) x 23.22" (D)

Dispense area height

22 cm-32 cm/ 8.66"-12.59" (adjustable)

Weight

Countertop: 105.8 lbs

Base cabinet: 46.7 lbs

Filtration*

High performance carbon filter

*Filter type depending on local water conditions

Storage capacity

Ice bath: 21 liters (4.61 gal)

Sparkling tank: 1 liter (0.21 gal)

Dispensing capacity

Up to 160L/h (42 gal/h)

Flow rate (P231 NSF/ANSI standard certified)

2.5-3.5 liter/min

Compressor

USA compressor (R134a): 220w

Water temperature output

Cold: 37.4-53.6°F

Sparkling: 37.4-53.6°F

Contact us today

Waterlogic Commercial Products, LLC
www.waterlogicdealers.com
(800) 288-1891
customerservice@waterlogicsusa.com

3175 Bass Pro Drive, Grapevine, TX 76051

Waterlogic International Limited and WLI Trading Limited reserve the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLI Trading Ltd licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

Tested and certified



The HORECA Firewall is certified by IAPMO R&T to NSF/ANSI 55 Class A, NSF P231, and US EPA Guide Standard and Protocol for Testing Microbiological Water Purifiers, and NSF 372 for lead free compliance.