



# WL3 Firewall<sup>®</sup>

Excellent purification performance  
in an elegant and convenient dispenser

## Refreshingly safe water for the workplace

The WL3 Firewall<sup>®</sup> (WL3 FW) by Waterlogic dispenses a choice of popular water types, including hot and extra hot options. Equipped with Firewall superior UVC purification technology, this unit guarantees you safe hydration and the best-tasting water.

## Advanced technology

The WL3 FW features three core technologies:



### High performance filtration

Waterlogic's filters are certified to stringent standards by IAPMO R&T, carrying the Water Quality Platinum Seal, meaning they offer the best possible filtration. This guarantees each drop is as good as the last.



### Firewall purification

Waterlogic's patented and certified Firewall UVC purification system thoroughly purifies the water all the way through to the point of dispense for microbiologically safe water. Tested effective against COVID-19 and guaranteed free from: up to 99.9999% bacteria, 99.99% viruses, and 99.9% cysts.



### BioCote<sup>®</sup> antimicrobial protection\*

The WL3 FW key surfaces are infused with BioCote<sup>®</sup>, a silver ion additive that inhibits the growth of odor and stain causing microbes, such as bacteria and mold.



## A contemporary design with the luxury of choice

The streamlined and stylish WL3 offers 4 different water temperatures to satisfy every hydration need. An endless supply of cold, refreshing water is the expected standard, while offering hot and extra hot allows for the addition of cocoas, soups, and herbal teas. The WL3 also offers the choice of ambient, as it is believed to be more easily absorbed by the body for optimal hydration and better digestion.

\*BioCote<sup>®</sup> silver ion technology protects surfaces from odor- and stain-causing microbes. BioCote<sup>®</sup> does not protect users or others against bacteria, viruses, germs or other disease causing organisms. This technology is not a substitute for good cleaning practices.

## Features

Firewall-patented UVC technology reduces the risks of bacteria, viruses, and pathogens, purifying the water up to 99.9999%. Rigorously tested\* and guaranteed effective at inactivating the human form of COVID-19 with a colony reduction of over 99.999%

[Independently tested by the University of Arizona's Water & Energy Sustainable Technology (WEST) Center.]

Standard touch sensitive control panel for easy operations

Hands-free dispensing enabled by pedal controls

For extra hot, press the hot button and hold for 10 seconds. Hot icon will flash slowly. When flashing stops, the extra hot water is ready to dispense. Press and release the hot button, which will cause the hot icon to flash rapidly, and then press the button again to dispense the extra hot water.

LED UV fault indicator for easier servicing and peace of mind

Energy-saving sleep mode reduces power consumption when the unit is not in use

## Water options

cold      sparkling      ambient      hot      extra hot



## Technical specifications

### Types available

Tower and countertop

### Dimensions (include feet)

Tower:

15.15" (W) x 44.88" (H) x 14.37" (D)

Countertop:

15.15" (W) x 17.48" (H) x 17.77" (D)

### Dispensing area height

9.25"

### Weight

Tower: ~66-75 lbs

Countertop: 59 lbs

### Recommended filtration

Carbon block (CBC) with lead, cyst, and asbestos reduction

### Storage capacity

Cold tank (Tower): 1.06 US gal.

Cold tank (Countertop): 0.53 US gal.

Hot tank (Tower): 0.4 US gal.

Hot tank (Countertop): 0.4 US gal.

### Compressor

120v 60Hz (R134a gas)

### Water temperatures settings

Cold: 41°F/5°C

Hot: 183.2°F/84°C

Extra Hot: 199.4°F /93°C

## Number of users 1 - 30

## Contact us today

Waterlogic Commercial Products, LLC

Tel: 800-288-1891

[waterlogicdealers.com](http://waterlogicdealers.com)

[customerservice@waterlogicausa.com](mailto:customerservice@waterlogicausa.com)

## Tested and certified



Firewall technology is certified by IAPMO R&T to NSF/ANSI 55 Class A, NSF P231, US EPA Microbiological Guide Standard, NSF/ANSI 372 and CSA B483.1.



\*certificate may vary depending on different models or products