

# WL1000GF Max

High performance water dispenser  
for great quality water



## Superior performance

The WL1000GF Max is able to satisfy high demand of cold water, even at peak times, dispensing high volumes of perfectly chilled water. The gravity fed system makes this machine ideal for areas with low water pressure or situations where incoming water conditions require the use of reverse osmosis.

## Advanced technology

The WL1000GF Max features three core technologies:



### High Performance Filtration

This model can be configured with a four stages reverse osmosis system or carbon filtration, depending on water conditions. These filtration processes effectively remove water contaminants and chlorine to improve water taste and odour.



### In-tank UV

Waterlogic's UV technology uses an in-tank UV system to effectively remove waterborne micro-organisms to guarantee the best quality water.



### BioCote® Protection

The key plastic surfaces surrounding the dispensing area are infused with BioCote®, a silver ion additive that provides continuous antimicrobial protection against a broad spectrum of potentially harmful bacteria, mould and fungi, and reduce the risks of cross-contamination.

## Simply great, clear water

**Free from chlorine** (dependent on filters type and water conditions)  
**Free from water-borne tastes and odours**  
**Free from bacteria**

## Features

Multiple filtration options: choice of reverse osmosis or carbon filtration to fit specific water conditions

Large chilled recirculating reservoir for high capacity cold water production

Gravity-fed system makes this machine ideal for reverse osmosis system or for low pressure installations

The recirculating cold water system ensures water is exposed to the in-tank UV light multiple times every hour to maintain the microbiological purity of the water

Programmable temperature settings for hot and cold options

GAC filter fitted inside the cold reservoir to provide ongoing protection from bad taste and odours

Faults indicators for easier servicing

BioCote® protected reservoir and dispensing area (including drip tray body, cold faucet, user interface panel and buttons)

Leak detection for peace of mind

Energy saving sleep mode

## Technical specifications

### Type available

Freestanding

### Dimensions

380 mm (W) x 1140 mm (H) x 340 mm (D)

### Dispense area height

230 mm

### Weight

28.1 kg

### Filtration

Reverse Osmosis or 1 x Carbon filtration

### Storage capacity

Chilled reservoir: 11.2 litres

Cold hybrid tank: 4 litres

Total cold capacity: 15.2 litres

Hot tank (500 Watt): 1.6 litres

85° C thermistor-controlled

### Compressor

1/10-hp, 90-Watt

### Pump recirculation rate

1 litre per minute

### Programmable water temperatures settings

Cold: 3°/ 5°/7° C (default set at 5°C)

Hot: 80°/ 85°/ 93° C (default set at 85°C)

### Dispensing capacity (Cold)

8 litres per hour\*

[\*Drawing water continuously until the cold water dispensed rises by 5°C]

## Water options

cold



sparkling

ambient

hot



extra hot

## Number of users



50+

## Tested and certified



**CE** QUALITY & SAFETY  
GUARANTEED

Waterlogic International Limited and WLI Trading Limited reserve the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLI Trading Ltd licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

## Call us today

**UK** + 44 (0) 333 323 2307  
[www.waterlogic.co.uk](http://www.waterlogic.co.uk)  
[enquiries@waterlogic.co.uk](mailto:enquiries@waterlogic.co.uk)

**Ireland** +353 1 466 0133  
[www.waterlogic.ie](http://www.waterlogic.ie)  
[info@waterlogic.ie](mailto:info@waterlogic.ie)

**USA & Canada** + 1 402 905 2001  
[www.waterlogicsusa.com](http://www.waterlogicsusa.com)  
[customerservice@waterlogicsusa.com](mailto:customerservice@waterlogicsusa.com)

**Rest of the World** + 353 1 293 1960  
[www.waterlogic.com](http://www.waterlogic.com)  
[exportsales@waterlogic.com](mailto:exportsales@waterlogic.com)

For more information, visit [www.waterlogic.com](http://www.waterlogic.com)