

# WL5 Firewall™

Excellent purifying performance, for high usage applications



## A plentiful supply of purified water

The WL5 Firewall satisfies the demand for the highest levels of hygiene and safety, and is ideal for places where high volume water dispensing is paramount.

## Advanced technology



### High performance filtration

Quality approved carbon block filters tested to the strictest health standards to ensure superior filtration is guaranteed for optimum taste.



### Firewall purification

Waterlogic's patented Firewall technology utilises a highly effective UVC purification system at the point of dispense. Firewall guarantees 99.9999% purified water. Glass after glass.



### Stainless steel finish

The robust and practical stainless steel finish provides maximum durability and hygiene, facilitating cleaning and making the machine ideal for high usage areas.

## High flow for high usage

WL5 FW is designed to ensure the maximum level of water purification is guaranteed on high flow still and sparkling water. With a dispensing capacity of up to 100 litres per hour, WL5 FW is a must-have for hydration demanding environments.

## Features

Firewall, patented UV technology reduces the risks of bacteria, viruses, and cysts purifying the water up to 99.9999%, 100% of the time

Dispensing area suitable to accommodate average size sport bottles

Touch sensitive buttons for smooth dispensing operation

Convenient portion control for filling bottles and carafes in busy environments

Optional wall bracket-fixing to protect against possible damage and incidents in high footfall areas

Carbonation level indicator to signal when CO<sub>2</sub> cylinder replacement is needed

Lockable base cabinet converts the unit from countertop to freestanding, and offers extra storage space for CO<sub>2</sub> cylinders

Drip tray overflow sensor to prevent the risk of accidents from water spillage

## Technical specifications

### Types available

Freestanding (with optional base cabinet)  
Countertop

### Dimensions

Freestanding:  
360 mm/14.17" (W) x 1370 mm/53.93" (H) x 500 mm/19.68" (D)  
Countertop:  
360 mm/14.17" (W) x 470 mm/19.50" (H) x 500 mm/19.68" (D)

### Dispensing area height

250 mm/ 9.84"

### Weight

Countertop: 40 Kg/ ~88 lbs  
Freestanding: 61 Kg/ ~134 lbs

### Standard filtration supplied

Carbon

### Cooling capacity

70 litres /h (~15 gal/h) at Δ 6°C  
60 litres /h (~13 gal/h) at Δ 5°C

### Dispensing capacity

100 litres/h (~22 gal/h)

### Compressor

1/5 HP

### Water temperature settings

Cold: 4-15°C / 39.2-59°F

## Water options



## Number of users



## Tested and certified

NSF/ANSI-55 Class A  
Ultraviolet Microbiological  
Water Treatment Systems  
NSF P231  
Protocol for  
Microbiological Purifiers



CE QUALITY & SAFETY  
GUARANTEED

\*certificate may vary depending on different models or products

Waterlogic International Limited and WLI Trading Limited reserve the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLI Trading Ltd licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

## Call us today

**UK** + 44 (0) 333 323 2307  
[www.waterlogic.co.uk](http://www.waterlogic.co.uk)  
[enquiries@waterlogic.co.uk](mailto:enquiries@waterlogic.co.uk)

**Ireland** + 353 1 466 0133  
[www.waterlogic.ie](http://www.waterlogic.ie)  
[info@waterlogic.ie](mailto:info@waterlogic.ie)

**USA & Canada** + 1 402 905 2001  
[www.waterlogicausa.com](http://www.waterlogicausa.com)  
[customerservice@waterlogicausa.com](mailto:customerservice@waterlogicausa.com)

**Rest of the World** + 353 1 293 1960  
[www.waterlogic.com](http://www.waterlogic.com)  
[exportsales@waterlogic.com](mailto:exportsales@waterlogic.com)

For more information, visit [www.waterlogic.com](http://www.waterlogic.com)