

WL Cube Firewall™

First class purification performance in a distinct compact unit

Excellent, thoroughly purified water for small workplaces

With its sophisticated and premium look, the WL Cube Firewall (WL Cube FW) is the ideal worktop solution for small working environments, meeting rooms, kitchens, bar and break areas.

Advanced technology

The WL Cube FW features three core technologies:



High performance filtration

Waterlogic's filters are certified to stringent standards, carrying the Water Quality Association's Gold Seal of approval, meaning they offer the best possible filtration.



Firewall

Waterlogic's patented Firewall technology utilises a highly effective UVC purification system at the point of dispense. Firewall guarantees 99.9999% purified water. Glass after glass.



BioCote® protection

The WL Cube FW key surfaces are infused with BioCote, a silver ion additive able to inhibit microbial growth on the surface of the products helping to reduce unpleasant odours, degradation of key surfaces and the potential for cross contamination.



Standard model








Expert purification

Featuring Firewall, which thoroughly purifies the water as it is dispensed, acting also as a barrier preventing back contamination from outside, the WL Cube FW is the only compact machine on the market delivering totally safe cold, ambient and sparkling water, cleansed from pathogens by up to 99.9999%.

Features

- Firewall, patented UV technology reduces the risks of bacteria, viruses, and cysts purifying the water up to 99.9999%, 100% of the time
- Removable drip tray to easily accommodate average size sport bottles
- Elegant touch sensitive control panel for ease of use
- Energy saving sleep mode to reduce power consumption when unit is not in use
- LED UV fault indicator for easier servicing and peace of mind
- BioCote® protected dispensing area

Water options

	cold	sparkling	ambient	hot	extra hot
1					
2					

Number of users

 1 - 7

Technical specifications

Types available

Countertop

Dimensions

Standard model
Cube: 296mm/11.6" (W) x 375mm/14.8" (H) x 425mm/16.7" (D)
Sparkling model
296mm/11.6" (W) x 376mm/14.8" (H) x 527mm/20.8" (D)

Dispensing area height

155mm/6.10" (with drip tray)
247mm/9.7" (without drip tray)

Weight

Standard model: 18 KG/ ~39 lbs
Sparkling model: 19 KG/ ~42 lbs

Standard filtration supplied

Carbon

Storage capacity

Standard model:
Cold tank 1.4 litre. Hot tank 1.3 litre
Sparkling model:
Cold tank 1.3 litre. Sparkling tank 0.5 litre

Water temperatures settings

Cold 5-15°C / 41-59°F
Hot 87-95°C / 188.6-203°F



Sparkling model

Tested and certified

NSF/ANSI-55 Class A
Ultraviolet Microbiological
Water Treatment Systems
NSF P231
Protocol for
Microbiological Purifiers



*certificate may vary depending on different models or products

Waterlogic International Limited and WLI Trading Limited reserve the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLI Trading Ltd licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

Call us today

UK www.waterlogic.co.uk
+ 44 (0) 333 323 2307
info@waterlogic.co.uk

Ireland www.waterlogic.ie
+ 353 1 466 0133
info@waterlogic.ie

USA and Canada www.waterlogicsusa.com
+ 1 402 905 2001
customerservice@waterlogicsusa.com

Rest of the World www.waterlogic.com
+ 353 1 293 1960
exportsales@waterlogic.com

For more information, visit www.waterlogic.com