

WL2000 IT

Performance worthy of an encore
and functional design for the workplace



R600a gas

**Zero
environmental
impact**

Safe, refreshing water for any working environment

With a choice of hot, cold, and ambient, the WL2000IT is a popular choice for offices and factories where a great quality water is required.

Advanced technology

The WL2000IT features three core technologies:



High performance filtration

Waterlogic's filters are certified to stringent standards, carrying the Water Quality Association's Gold Seal of approval, meaning they offer the best possible filtration. This guarantees each drop is as good as the last.



In-tank UV

Waterlogic's in-tank UV technology acts against waterborne micro-organisms and bacteria, dispensing great quality water glass after glass.



BioCote® protection

The key plastic surfaces surrounding the dispensing area are infused with BioCote®, a silver ion additive that provides continuous antimicrobial protection against a broad spectrum of potentially harmful bacteria, mould and fungi, and reduces the risks of cross-contamination.

Safe water guaranteed

Our professional grade UV light purification removes bacteria from the water. UV purification safely cleanses the water without the need for toxic chemicals, so that you can enjoy refreshing great tasting water in every glass.

Features

In-tank UV technology is highly effective against germs and bacteria. A UV lamp treats the water stored in the reservoir for fast, reliable and easy water purification





Environmentally friendly refrigeration available with R600a: natural occurring refrigerating gas with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential)

Generous drip tray capacity for accidental spillage

BioCote® protected dispensing area

Thermal overload protection

Water options

	cold	sparkling	ambient	hot	extra hot
1					
2					

Number of users

 10 - 30

Technical specifications

Types available

Freestanding and countertop

Dimensions

Freestanding:

345 mm/13.6" (W) x 1030 mm/40.6" (H) x 367 mm/14.5" (D)

Countertop:

345 mm/13.6" (W) x 480 mm/18.9" (H) x 367 mm/14.5" (D)

Dispensing area height

215mm/ 8.5"

Weight (Hot and cold models)

Countertop: 22-23 KG/ ~48.5-50.7 lbs

Freestanding: 27-29 KG/ ~59-61 lbs

Standard filtration supplied

Carbon

Storage capacity

Hot tank: 1.5 litres (0.4 US gal.)

Cold tank (Freestanding): 4 litres (1.06 US gal.)

Cold tank (Countertop): 2 litres (0.53 US gal.)

Drip tray capacity

1.5 litres (0.4 US gal.)

Compressor

Compressor (R600a 1/8HP) 230V/50Hz

Water temperatures settings

Cold: 5-8°C/ 41-46.4°F (default 5°C/ 41°F)

Hot: 85-87°C/ 185-189°F (default 87°C)

Tested and certified



QUALITY & SAFETY
GUARANTEED

Waterlogic International Limited and WLI Trading Limited reserve the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLI Trading Ltd licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

Call us today

UK + 44 (0) 333 323 2307
www.waterlogic.co.uk
enquiries@waterlogic.co.uk

Ireland +353 1 466 0133
www.waterlogic.ie
info@waterlogic.ie

USA & Canada + 1 402 905 2001
www.waterlogicsusa.com
customerservice@waterlogicsusa.com

Rest of the World + 353 1 293 1960
www.waterlogic.com
exportsales@waterlogic.com

For more information, visit www.waterlogic.com