

WL4 Firewall™

Breakthrough purification technology,
proven performance and premium design



R600a gas

**Zero
environmental
impact**

*R600a gas available
on 220/240v models only

High-end, features rich dispenser for the workplace

A wide variety of features and water options in a premium dispenser, offering the best filtration and purification available, for the needs of the most sophisticated and demanding workplaces.

Advanced technology

The WL4 Firewall (WL4 FW) features three core technologies:



High performance filtration

Waterlogic's filters are certified to stringent standards, carrying the Water Quality Association's Gold Seal of approval, meaning they offer the best possible filtration. This guarantees each drop is as good as the last.



Firewall

Waterlogic's patented Firewall technology utilises a highly effective UVC purification system at the point of dispense. Firewall guarantees 99.9999% purified water. Glass after glass.



BioCote® protection

The WL4 FW key surfaces are infused with BioCote, a silver ion additive able to inhibit microbial growth on the surface of the products helping to reduce unpleasant odours, degradation of key surfaces and the potential for cross contamination.

Excellent performance with safety in mind

Built-in safety features and outstanding purification performance, make the WL4 FW the ideal water dispenser to satisfy the hydration needs of the modern working environment, where the safeguard of Health and Safety is paramount.

Features

Firewall, patented UV technology reduces the risks of bacteria, viruses, and cysts purifying the water up to 99.9999%, 100% of the time
Superior quality sparkling water, safely purified to NSF standards
Modular base cabinet converts the unit from countertop to freestanding, and offers filter and CO ₂ storage space
Thermal cut-out and leak prevention systems provide extra safety and reduces risks of accident
Energy saving sleep mode to lower power consumption when the unit is not in use
Intuitive User Interface panel featuring LED icons, operating buttons and mood lighting
Built-in drip tray sensor to prevent the risk of overflow
Integrated cup dispenser (available on freestanding version only)
LED UV fault indicators for easier servicing and peace of mind
BioCote protected dispensing area

Technical specifications

Types available

Freestanding and countertop

Dimensions

Freestanding:
418mm/16.5" (W) x 1238mm/48.7" (H) x 470mm/18.5" (D)
Countertop:
417mm/16.4" (W) x 439mm/17.3" (H) x 470mm/18.5" (D)

Dispensing area height

240mm/ 9.5"

Weight (Hot and cold models)

Countertop: 24-35 KG/ ~53-77 lbs
Freestanding: 42-53 KG/ ~92-117 lbs

Standard filtration supplied

Carbon

Storage capacity

Hot tank: 1.2 liters (0.317 US gal.)
Cold tank: 4.5 liters (1.19 US gal.)
















Compressor

220/240v 50Hz or 110/120v 60Hz

Water temperatures settings

Cold 6°-9°C/ 41°-48.2°F
Hot 87°C/ 189°F
Extra hot 93°C/ 207°F

Water options

	cold	sparkling	ambient	hot	extra hot
1					
2					
3					
4					
5					
6					

Number of users

 30 - 50



Tested and certified

NSF/ANSI-55 Class A
Ultraviolet Microbiological
Water Treatment Systems
NSF P231
Protocol for
Microbiological Purifiers



*certificate may vary depending on different models or products

Waterlogic International Limited and WLI Trading Limited reserve the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLI Trading Ltd licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

Call us today

UK www.waterlogic.co.uk
+ 44 (0) 333 323 2307
info@waterlogic.co.uk

Ireland www.waterlogic.ie
+ 353 1 466 0133
info@waterlogic.ie

USA and Canada www.waterlogicsusa.com
+ 1 402 905 2001
customerservice@waterlogicsusa.com

Rest of the World www.waterlogic.com
+ 353 1 293 1960
exportsales@waterlogic.com

For more information, visit www.waterlogic.com