

# WL850

## Quality water and sturdy, functional design



### Robust and reliable performance for demanding workplaces

WL850 is ideal for satisfying even the heaviest demand for quality drinking water. With a selection of cold, sparkling, ambient and hot water, it offers the workforce pure, invigorating water for greater productivity and better focus all day long.

### Advanced technology

The WL850 features three core technologies:



#### High performance filtration

Waterlogic's filters are certified to stringent standards, carrying the Water Quality Association's Gold Seal of approval, meaning they offer the best possible filtration. This guarantees each drop is as good as the last.



#### In-tank UV sanitisation

Waterlogic's in-tank UV technology acts against waterborne micro-organisms and bacteria dispensing great quality water glass after glass.



#### BioCote® protection

The key plastic surfaces surrounding the dispensing area are infused with BioCote®, a silver ion additive that provides continuous antimicrobial protection against a broad spectrum of bacteria, mould and fungi, and reduces the risk of cross-contamination.

### Safe water guaranteed

UV light sanitisation wipes out bacteria from the water tank, by destroying the DNA core, eliminating E. Coli, Salmonella and Hepatitis, to name a few. UV purification safely cleanses the water without the need for toxic chemicals.

## Features

In-tank UV technology is highly effective against germs and bacteria. A UV lamp treats the water stored in the reservoir with doses of UV energy for fast, reliable and easy water sanitisation

Tall dispensing area suitable for accommodating sports bottles, jugs and carafes

Robust design and durable materials particularly suitable for demanding environments. Ideal for factories and warehouses

Generous drip tray capacity for accidental spillage

LED UV lamp and hot and cold fault indicators for easier servicing

BioCote® protected dispensing area (including drip tray body, cold faucet and dispensing buttons)

Thermal overload alarm and leak prevention systems provide extra safety and reduce accident risks

## Technical specifications

### Types available

Freestanding and countertop

### Dimensions

Freestanding:

380 mm/14.96" (W) x 1140 mm/44.88" (H) x 340 mm/13.38" (D)

Countertop:

380 mm/14.96" (W) x 470 mm/18.50" (H) x 340 mm/13.38" (D)

### Dispense area height

240 mm/ 9.5"

### Weight

Freestanding: 40 Kg/ ~88 lbs

Countertop: 29 Kg/ ~61 lbs

### Standard filtration supplied

Carbon

### Storage capacity

Hot tank: 1.4 litres (0.3 US gal)

Cold tank: 2 litres (0.53 US gal)

Sparkling tank: 2 litres (0.53 US gal)

### Compressor








230V (50Hz)/ 110v (60Hz) compressor

### Water temperature settings

Cold: 5°C/41°F

Hot: 87°C/189°F

## Water options

	cold	sparkling	ambient	hot	extra hot
1					
2					
3					

\*Hot option not available in countertop models

## Number of users



10 - 30



## Tested and certified



QUALITY & SAFETY  
GUARANTEED

Waterlogic International Limited and WLI Trading Limited reserve the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLI Trading Ltd licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

## Call us today

UK [www.waterlogic.co.uk](http://www.waterlogic.co.uk)

+ 44 (0) 333 323 2307

info@waterlogic.co.uk

Ireland [www.waterlogic.ie](http://www.waterlogic.ie)

+ 353 1 466 0133

info@waterlogic.ie

USA and Canada [www.waterlogicausa.com](http://www.waterlogicausa.com)

+ 1 402 905 2001

customerservice@waterlogicausa.com

Rest of the World [www.waterlogic.com](http://www.waterlogic.com)

+ 353 1 293 1960

exportsales@waterlogic.com

For more information, visit [www.waterlogic.com](http://www.waterlogic.com)